



PROPANE HOSE

TUBE	Oil Resistant Synthetic Rubber Compound
REINFORCEMENT	High Strength Synthetic Textile Braiding
COVER	Smooth or Fluted Oil, Ozone & Abrasion
APPLICATIONS	For Transfer of Propane Gas
PROPERTIES	High Abrasion Resistance / Uniform Thickness / Flexible
STANDARD COLOUR	Inner Tube - Black , Outer Cover - Orange
FINISH	Smooth/Wrapped / Fluted
STANDARD	AS PER IS 447/EN-559/RMA: IP-7-2008

PART NO.	Internal Diameter		Outer Diameter	Working Pressure		Bursting Pressure		Weight	Std. Length
EPRH-06	Inch	mm	mm	bar	psi	bar	psi	Kg/m	mtr
	1/4	6	13	20	300	60	900	0.155	100/50
EPRH-08	Inch	mm	mm	bar	psi	bar	psi	Kg/m	mtr
	5/16	8	15	20	300	60	900	0.200	100/50
EPRH-10	Inch	mm	mm	bar	psi	bar	psi	Kg/m	mtr
	3/8	10	17	20	300	60	900	0.220	100/50

Note: Available in Reel Packing/Shrink Box Packing in 25/50/100 Feet with & without fitting